



HEATECO CLOUD WITH CONTROL VIA INTERNET (CN 031)

CN 031 250 EI CLOUD W



Net weight	9.64 kg
Maximum power	2500 W
Thermo regulator	electronic
For room up to	50-70 m ³
Heating area	20-28 m ²
Height	0.45 m
Depth	0.09 m
Control via internet	yes
Where in the room the appliance will be installed?	На вътрешна стена



Information

CN 031 250 EI CLOUD W

- Maximum power : 2500 W
- Optimal convection - up to 25% faster room heating
- Precise thermoregulator with an accuracy of 0.1°C
- Electronic thermoregulator 10-30°C
- Up to 21% lower electricity costs
- Thermostat calibration to achieve the desired comfort - temperature correction $\pm 4^{\circ}\text{C}$
- Build-in IEEE 802.11 b/g/n Wi-Fi module for control via Internet
- Weekly programmer 24h/7d with 30-minute step
- Adaptive start with on/off option - provides optimal comfort and saves energy
- Bathroom installation option - splash proof IP24 protection
- Delay start function - 96 hours
- Anti-frost protection, fixed on 5°C, with on/off option
- Keyboard lock / children protection
- Overheating protection
- LED display indicating desired and actual room temperature
- Robust metal construction

Serie information

CN 031 250 EI CLOUD W

HeatEco electric panel convectors with control via Internet achieve 39% of maximum 40% Seasonal Energy Efficiency. This is reached thanks to the electronic thermoregulator and ERP related functions ("smart" functions), which save energy and are easy to use. Smart functions include: Open Window/Door Detection; Adaptive Start; Temperature Sensor Correction $\pm 4^{\circ}\text{C}$, Control Via Internet, Weekly Programmer 24/7.